HILLYARD The Cleaning Resource*

SAFETY DATA SHEET

1. Identification

Product identifier DEVASTATOR

Other means of identification

SDS number 540N-22A
Product code HIL00147
Recommended use Stripper

Recommended restrictions For Labeled Use Only **Manufacturer/Importer/Supplier/Distributor information**

Manufacturer Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.

St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or

accident involving chemicals)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, dermal

Acute toxicity, inhalation

Skin corrosion/irritation

Category 4

Category 4

Category 4

Category 1

Serious eye damage/eye irritation

Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage.

Causes serious eye damage. Harmful if inhaled. Harmful to aquatic life.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Material name: DEVASTATOR SDS US

HIL00147 Version #: 02 Revision date: 04-22-2016 Issue date: 04-01-2015

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Buyer assumes all risk and liability associated with disposal of this product (original concentration Disposal

or dilution) in violation of applicable law in compliance with applicable federal, state and local

requirements.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------------------------|--------------------------|------------|-----------|
| Ethylene glycol monobutyl ether | | 111-76-2 | 20 - < 30 |
| Benzyl Alcohol | | 100-51-6 | 5 - < 10 |
| Ethanol, 2-amino- | | 141-43-5 | 5 - < 10 |
| Other components below reportable | e levels | | 60 - < 70 |

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or Skin contact

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delaved

Indication of immediate medical attention and special

treatment needed

General information

Burning pain and severe corrosive skin damage. Permanent eye damage including blindness could result. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Powder. Alcohol resistant foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

Material name: DEVASTATOR SDS US

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. This product is miscible in water. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Never return spills to original containers for re-use.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid prolonged exposure. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Value

5 ppm

Value

44.2 mg/m3

6 mg/m3

8. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Type

PEL

Occupational exposure limits

Ethanol, 2-amino- (CAS

ether (CAS 111-76-2)

Benzyl Alcohol (CAS

Components

100-51-6)

Components

| 141-43-5) | | | |
|--|---------------|--------------|--|
| | | 3 ppm | |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | PEL | 240 mg/m3 | |
| | | 50 ppm | |
| US. ACGIH Threshold Limit Value | s | | |
| Components | Туре | Value | |
| Ethanol, 2-amino- (CAS 141-43-5) | STEL | 6 ppm | |
| , | TWA | 3 ppm | |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | TWA | 20 ppm | |
| US. NIOSH: Pocket Guide to Cher | nical Hazards | | |
| Components | Туре | Value | |
| Ethanol, 2-amino- (CAS 141-43-5) | STEL | 15 mg/m3 | |
| • | | 6 ppm | |
| | TWA | 8 mg/m3 | |
| | | 3 ppm | |
| Ethylene glycol monobutyl | TWA | 24 mg/m3 | |
| | | -····g·····• | |

Material name: DEVASTATOR SDS US

HIL00147 Version #: 02 Revision date: 04-22-2016 Issue date: 04-01-2015

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Type

TWA

Components Value Type

10 ppm

Biological limit values

| ACGIH I | Biological | Exposure | Indices |
|---------|------------|----------|---------|
|---------|------------|----------|---------|

| Components | Value | Determinant | Specimen | Sampling Time |
|--|----------|--|---------------------|---------------|
| Ethylene glycol monobutyl ether (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | * |

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene glycol monobutyl ether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing Not normally required with adequate ventilation. Respiratory protection

Thermal hazards None known.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear, colorless liquid

Physical state Liquid. **Form** Liquid. Color Not available. Mild solvent odor Odor Not available. **Odor threshold**

pН 11 - 12

Melting point/freezing point Not applicable / Not available

210 °F (98.89 °C) Initial boiling point and boiling

range

> 200.0 °F (> 93.3 °C) Tag Closed Cup Flash point

< 1 Ethyl ether = 1 **Evaporation rate** Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%)

16 mm Hg Vapor pressure

Material name: DEVASTATOR HIL00147 Version #: 02 Revision date: 04-22-2016 Issue date: 04-01-2015 Vapor density 1.6 Air=1
Relative density 0.998 at 77°F

Solubility(ies)

Solubility (water) Appreciable

Partition coefficient Not available

(n-octanol/water)

Auto-ignition temperatureNot availableDecomposition temperatureNot availableViscosityNot available

Other information

Density 8.31 lb/gal
Explosive properties Not explosive.
Oxidizing properties Not oxidizing.
Percent volatile 97 - 98 %
VOC 27 % CARB
34.2 % US EPA

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes severe skin burns. Harmful in contact with skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and

toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Permanent eye damage including blindness could result. Symptoms may include stinging, tearing, redness,

swelling, and blurred vision. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and

central nervous system effects. Harmful if inhaled. Harmful in contact with skin. Harmful if

swallowed. May cause respiratory irritation.

Product Species Test Results

DEVASTATOR

Acute Dermal

LD50 Rabbit 70000 ml/kg estimated

1652 mg/kg estimated

Material name: DEVASTATOR SDS US

| Product | Species | Test Results |
|----------------------------|---------------------|-------------------------------|
| Inhalation | | |
| LC100 | Rat | 2924 mg/l, 8 Hours estimated |
| LC50 | Mouse | 3465 ppm, 7 Hours estimated |
| | Rat | 14620 mg/l, 8 Hours estimated |
| | | 2228 ppm, 4 Hours estimated |
| Oral | | |
| LD50 | Guinea pig | 5.9 g/kg estimated |
| | Mouse | 5.9 g/kg estimated |
| | Rabbit | 1.6 g/kg estimated |
| | Rat | 2401 mg/kg estimated |
| Components | Species | Test Results |
| Benzyl Alcohol (CAS 100-51 | 1-6) | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | 2000 mg/kg |
| Inhalation | | |
| LC100 | Rat | 200 - 300 mg/l, 8 Hours |
| LC50 | Rat | 1000 mg/l, 8 Hours |
| Oral | | 4 |
| LD50 | Mouse | 1580 mg/kg |
| | Rabbit | 1940 mg/kg |
| | Rat | 1230 - 3100 mg/kg |
| thylene glycol monobutyl e | ther (CAS 111-76-2) | |
| Acute . | | |
| Dermal LD50 | Rabbit | 400 mg/kg |
| | Rabbit | 400 mg/kg |
| Inhalation LC50 | Mouse | 700 ppm, 7 Hours |
| 2000 | Rat | 450 ppm, 4 Hours |
| Orol | Nat | 430 ppm, 4 mours |
| Oral LD50 | Guinea pig | 1.2 g/kg |
| 2500 | Mouse | 1.2 g/kg |
| | Rabbit | 0.32 g/kg |
| | ιλαυνιι | U.UZ YINY |

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene glycol monobutyl ether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Material name: DEVASTATOR SDS US

Estimates for product may be based on additional component data not shown.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

| Product Species | | Species | Test Results | |
|----------------------|---------------------|--------------------------------|-------------------------------------|--|
| DEVASTATOR | | | | |
| Aquatic | | | | |
| Crustacea | EC50 | Daphnia | 99737.1328 mg/l, 48 hours estimated | |
| Fish | LC50 | Fish | 1306.0464 mg/l, 96 hours estimated | |
| Components | | Species | Test Results | |
| Benzyl Alcohol (CAS | 100-51-6) | | | |
| Aquatic | | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 10 mg/l, 96 hours | |
| Ethylene glycol mono | butyl ether (CAS 11 | 1-76-2) | | |
| Aquatic | | | | |
| | | | | |

Inland silverside (Menidia beryllina)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Fish

Partition coefficient n-octanol / water (log Kow)

Benzyl Alcohol 1.1 0.83 Ethylene glycol monobutyl ether

LC50

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

1250 mg/l, 96 hours

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Buyer assumes all risk and liability associated

with disposal of this product (original concentration or dilution) in violation of applicable law.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

Contaminated packaging

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Waste from normal product use may be sewered to a public owned treatment works (POTW) in

compliance with applicable Federal, State, and local pretreatment requirements.

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

Material name: DEVASTATOR

^{*} Estimates for product may be based on additional component data not shown.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Ethylene glycol monobutyl ether (CAS 111-76-2)

US. Massachusetts RTK - Substance List

Benzyl Alcohol (CAS 100-51-6)

Ethanol, 2-amino- (CAS 141-43-5)

Ethylene glycol monobutyl ether (CAS 111-76-2)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol, 2-amino- (CAS 141-43-5)

Ethylene glycol monobutyl ether (CAS 111-76-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzyl Alcohol (CAS 100-51-6)

Ethanol, 2-amino- (CAS 141-43-5)

Ethylene glycol monobutyl ether (CAS 111-76-2)

US. Rhode Island RTK

Not regulated.

Material name: DEVASTATOR SDS US

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 04-01-2015

 Revision date
 04-22-2016

Version # 02

HMIS® ratings Health: 3

Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: DEVASTATOR SDS US