

product information

VAC "N" STRIP Rinse Free/Machineless WAX AND FINISH STRIPPER

DESCRIPTION: Strip "N" Vac represents state of the art technology in the development of Wax & Finish Removers. When used according to directions this product can remove wax and finish without the need for mechanical agitation or rinsing.

Strip "N" Vac can remove multi coats of high solids, burnished floor finish. When used with a wet and dry pick up Vac., this product NEVER requires rinsing.

SPECIFICATION:

Color Blue

Odor Bland

pH 11

Flash Point None

Viscosity Free Flowing

Solubility in Water Complete

Specific Gravity 1.01

Wt. per Gal. 8.39-8.43

Stability One Year Minimum

UNCLE SAM CHEMICAL COMPANY CO., INC. 573-577 W. 131 St., New York, N.Y. 10027-7901

MATERIAL SAFETY DATA SHEET

PRODUCT # C323-05P

ND = Not Determined, NE = Not Established, NA = Not Applicable

SECTION 1 - PRODUCT IDENTIFICATION

NPCA Iluzurdous Materials Identification System

oduct Name: EEZEE-GO RINSE FREE FINISII & WAX STRIPPER

Generic Name: RINSE FREE STRIPPER

Proper Shipping Name: LIQUID CLEANING COMPOUND NOS

Precautious/Warnings: Eye & Skin Irritant. Keep Out Of The Reach Of Children

Q
0

Tel: (212) 281-6100 (800) 388-8809

FAX: (212) 368-7055

SECTION 2 - INGREDIENTS						
CHEMICAL NAME	CAS No.	WT.%	OSHA-PEL	ACGIII-TLV		
Sodium Hexametaphosphate	68915-31-1	0.5-1.5	NA	NA		
2 Hydroxyethylamine	141-43-5	10-15	NE	NE		
2 Butoxyethanol	111-76-2*	8-10	NE	25(skin)		
Fragrance	Proprietory	0.1-0.3	NA	NA		
Water	7732-18-5	Q.S.	NA	NA		

SECTION 3 - PHYSICAL DATA

Boiling Point: 212°F Specific Gravity: 1.007

Vapor Pressure(mm Hg): <17 Vapor Density: >1

pli (Couc.): 10 Solubity in Water: Infinite

% Volatile: 98.8 Wt. per Gallon: 8.36

Appearance & Odor: Clear, It. blue color liquid; pleasant mint/fl odor

Evaporation Rate: <1

SECTION 4 - FIRE AND EXPLOSION DATA

Flash Point: Greater than 212° F. Explosive Limits: NA

Extinguishing Media: Product is non-flammable

Special Fire Fighting Procedures: None

Unusual Fire & Explosion Hazards: None

SECTION 5 - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: Will not occur

Incompatibility (Material to Avoid): Strong acids & bases

Hazardous Decomposition Products: NA

SECTION 6 - STORAGE AND HANDLING INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE
Keep out of the reach of children. For use by trained personnel only
Keep container closed during storage. For institutional & industrial

use only.

Keep from freezing. Product may coagulate. Storage Temperatures: Max. 140 F. Mis. 34 F.

SECTION 7 - HEALTH HAZARDS AND FIRST AID

'FECTS OF OVEREXPOSURE

/ES: Slightly irritating to eyes.

SKIN: May irritate on repeated or prolonged contact.

INIIALATION: Vapor or mist can cause headache, nausea & irritation

of the eyes, nose, throat & lungs.

INGESTION: May cause irritation to mouth, esophagus, & stomach.

CARCINOGENIC: Non-carcinogenic

FIRST AID PROCEDURE

EYES: Flush eyes with large amount of water for at least 15 minutes, get medical help if redness persists.

SKIN: Wash affected areas with soap and water.

INHALATION: Move subject to fresh eir.

INGESTION: Induce vomiting. Seek medical help.

SECTION 8 - SPILL, LEAKS & DISPOSAL PROCEDURES

SMALL SPILLS: Absorb spill on inert material sand, earth, etc. and dispose of as waste materials.

LARGE SPILLS: Keep spectators away. Floors may be slippery. Use care to avoid falling. Dike and maintain spill with inert material. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoffs out of municipal sewers & open dodies of water.

WASTE DISPOSAL: Coagulate the emulsion by stepwise addition of ferric chloride or lime. Remove the clear supernatant liquid and flush to a chemical sewer. Landfill or incinerate the solids and the contaminated diking material according to local, state & federal regulations.

SECTION 9 - SPECIAL PROTECTION INFORMATION

EYE PROTECTION: Chemical splash goggles (ANS Z-87-1 or approved equivalent).

RESPIRATORY PROTECTION: None required if good ventilation is maintained. Otherwise, wear self contained breathing apparatus (pressure demand, MSIIA/NIOSH approved or equivalent).

PROTECTIVE GLOVES: Impervious

ENTILATION: Mechanical local exhaust ventilation at point of contaminant release.

SECTION 10 - TOXICITY INFORMATION

[•] This product contains 2-Butoxyethanol, a toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments & Reauthorizatin Act of 1986 & 40 CFR Part 372.

ABBREVIATIONS

CAS Chemical Abstracts Service Number

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety and Health Administration

TLV Threshhold Limit Value PEL Permissible Exposure Limit TWA Time Weighted Average Exposure

STEL Short-Term Exposure Limit

IMPORTANT: The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true and accurate to the best of our knowledge. No WARRANTY, OR GUARANTEE, EXPRESSED OR IMPLIED IS MADE REGUARDING PERFORMANCE, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling and storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions reguarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or violate any Federal, State or Local Lawe.

Date Material Data Sheet Prepared

This MSDS has been prepared in accordance with OSHA Hazard Comunication Standard (29 CRF 1910 1200).